



General

LHD and RHD options available
545
1325
600
2
6
Injection molded DCPD
Vacuum formed ABS

Performance

Gradebility (%)	20
Maximum Forward Speed (km/h)	25
Maximum Reverse Speed (km/h)	6
Minimum turning radius (m)	4.8
Outside Clearance Circle (m)	9.7

Dimension

Overall Length (mm)	3755
Overall Width (mm)	1315 (Alloy Rim)
Overall Height (mm)	1930
Wheelbase (mm)	2165
Floor Board Height (mm)	332
Ground Clearance (mm)	156
Tire Size (mm)	215/50-R12
Front Wheel Track (mm)	1100 (Alloy Rim)
Rear Wheel Track (mm)	1090 (Alloy Rim)
Tread - Front and Rear	Symmetric tread with P825 Pattern
Cup holder (cm³)	600
Glove Box (cm³)	2700
Mobile Tray (cm³)	288
Available Model Colors	Traffic White, Blue, Black, Burnt Crimson and Rally Red
Available Seat Color	Brown, Black
Available Suntop Color	White, Black
Headlights / Rear Lights	LED



Chassis

Frame	ladder-style steel frame
Steering	Self-compensating double reduction helical rack-and-pinion gear box
Front Wheel Suspension	Double wishbone
Rear Wheel Suspension	Leaf spring
Suspension	hydraulic shock absorbers
Bumpers	Vacuum formed ABS
Park Brake	Auto Electromagnetic
Service Brake - Front	Hydraulic - Disc
Service Brake - Rear	Hydraulic - Self-adjusting Drum

Battery

Battery	Not Included
Controller - Battery (A)	350
Charger	On Board Charger
Wiring Kit Type	Lead acid / Li-ion

Drive Train

Motor	3 Phase AC Inc	duction Motor with EM brake
Horse Power (hp)		6.7
Output Rating (kW)		5
Motor Control Unit (A)		350
Max. Speed (km/h)		25
Drive Train		Motor shaft direct drive
Transaxle	[Differential with Helical gears

Optional Accessories

Steel Wheel
TPMS (Tire Pressure Monitoring System)

Warranty

Warranty (year)	1
Warranty Policy	On Manufacturing Defect Only