

## **General**

LHD and RHD options available
640
1620
800
2
8
Injection molded DCPD
Vacuum formed ABS

## **Performance**

Gradebility (%)	20
Maximum Forward Speed (km/h)	25
Maximum Reverse Speed (km/h)	6
Minimum turning radius (m)	6.4
Outside Clearance Circle (m)	12.9

# **Dimension**

Overall Length (mm)	4600
Overall Width (mm)	1315 (Alloy Rim)
Overall Height (mm)	1930
Wheelbase (mm)	3025
Floor Board Height (mm)	332
Ground Clearance (mm)	156
Tire Size (mm)	215/50-R12
Front Wheel Track (mm)	1100 (Alloy Rim)
Rear Wheel Track (mm)	1090 (Alloy Rim)
Tread - Front and Rear	Symmetric tread with P825 Pattern
Cup holder (cm³)	600
Glove Box (cm³)	2700
Mobile Tray (cm³)	288
Headlights / Rear Lights	LED
Available Model Colors	Traffic White, Blue, Black, Burnt Crimson and Rally Red
Available Seat Color	Brown, Black
Available Suntop Color	White, Black

#### Chassis

Frame	ladder-style steel frame
Steering	Self-compensating double reduction helical rack-and-pinion gear box
Front Wheel Suspension	Double wishbone
Rear Wheel Suspension	Leaf spring
Suspension	hydraulic shock absorbers
Bumpers	Vacuum formed ABS
Park Brake	Auto Electromagnetic
Service Brake - Front	Hydraulic - Disc
Service Brake - Rear	Hydraulic - Self-adjusting Drum

### **Battery**

Battery	Not Included
Controller - Battery (A)	400
Charger	On Board Charger
Wiring Kit Type	Lead acid / Li-ion

### **Drive Train**

Motor	3 Phase AC Induction Motor with EM brake
Horse Power (hp)	6.7
Output Rating (kW)	5
Motor Control Unit (A)	400
Max. Speed (km/h)	25
Drive Train	Motor shaft direct drive
Transaxle	Differential with Helical gears

# **Optional Accessories**

Steel Wheel
TPMS (Tire Pressure Monitoring System)

# Warranty

Warranty (year)	1
Warranty Policy	On Manufacturing Defect Only