



General

LHD and RHD options available
600
1440
660
2
6
Injection molded DCPD
Vacuum formed ABS

Performance

Gradebility (%)	20
Maximum Forward Speed (km/h)	25
Maximum Reverse Speed (km/h)	6
Minimum turning radius (m)	6.4
Outside Clearance Circle (m)	12.9

Dimension

Overall Length (mm)	3950
Overall Width (mm)	1240
Overall Height (mm)	1930
Wheelbase (mm)	3025
Floor Board Height (mm)	334
Ground Clearance (mm)	156
Tire Size (mm)	145/80-R12
Front Wheel Track (mm)	1065
Rear Wheel Track (mm)	1055
Tread - Front and Rear	Symmetric tread with P825 Pattern
Cup holder (cm³)	600
Glove Box (cm³)	2700
Mobile Tray (cm³)	288
Headlights / Rear Lights	LED
Available Model Colors	Traffic White, Blue, Black, Burnt Crimson and Rally Red
Available Seat Color	Brown, Black
Available Suntop Color	White, Black

Chassis

ladder-style steel frame
Self-compensating double reduction helical rack-and-pinion gear box
Double wishbone
Leaf spring
hydraulic shock absorbers
Vacuum formed ABS
Auto Electromagnetic
Hydraulic - Disc
Hydraulic - Self-adjusting Drum

Battery

Battery	Not Included
Controller - Battery (A)	350
Charger	On Board Charger
Wiring Kit Type	Lead acid / Li-ion

Drive Train

Motor	3 Phase AC Induction Motor with EM brake
Horse Power (hp)	6.7
Output Rating (kW)	5
Motor Control Unit (A)	350
Max. Speed (km/h)	25
Drive Train	Motor shaft direct drive
Transaxle	Differential with Helical gears

Optional Accessories

Steel Wheel

TPMS (Tire Pressure Monitoring System)

Warranty

Warranty (year)	1
Warranty Policy	On Manufacturing Defect Only