



General

| Drive | LHD and RHD options available |
|-----------------------------|-------------------------------|
| Key or Pedal Start | Pedal Start |
| Dry Weight (kg) | 575 |
| Total Vehicle Capacity (kg) | 1605 |
| Vehicle Load Capacity (kg) | 850 |
| Cargo Box Material | Aluminum |
| Cargo Bed Capacity | 650 |
| Cup holders (No.) | 2 |
| Seating Capacity (No.) | 2 |
| Body and Finish (Front) | Injection molded DCPD |
| Body and Finish (Rear) | Vacuum formed ABS |

Performance

| Gradebility (%) | 20 |
|------------------------------|------|
| Maximum Forward Speed (km/h) | 25 |
| Maximum Reverse Speed (km/h) | 6 |
| Minimum turning radius (m) | 6.4 |
| Outside Clearance Circle (m) | 12.9 |
| | |

Dimension

| Overall Length (mm) | 4190 |
|--------------------------|--|
| Overall Width (mm) | 1240 |
| Overall Height (mm) | 1940 |
| Wheelbase (mm) | 3025 |
| Floor Board Height (mm) | 334 |
| Cargo Bed Dimension (mm) | 2135 x 1173 x 274 |
| Ground Clearance (mm) | 156 |
| Tire Size (mm) | 145/80-R12 |
| Front Wheel Track (mm) | 1065 |
| Rear Wheel Track (mm) | 1055 |
| Tread - Front and Rear | Symmetric tread with P825 Pattern |
| Cup holder (cm³) | 600 |
| Glove Box (cm³) | 2700 |
| Mobile Tray (cm³) | 288 |
| Headlights / Rear Lights | LED |
| Available Model Colors | Traffic White, Blue, Black, Burnt Crimson and Rally Red |
| Available Seat Color | Brown, Black |
| Available Suntop Color | White, Black |
| | |



Chassis

| ladder-style steel frame |
|---|
| Self-compensating double reduction helical rack-and-pinion gear box |
| Double wishbone |
| Leaf spring |
| hydraulic shock absorbers |
| Vacuum formed ABS |
| Auto Electromagnetic |
| Hydraulic - Disc |
| Hydraulic - Self-adjusting Drum |
| |

Battery

| Battery | Not Included |
|--------------------------|--------------------|
| Controller - Battery (A) | 400 |
| Charger | On Board Charger |
| Wiring Kit Type | Lead acid / Li-ion |

Drive Train

| Motor | 3 Phase AC Induction Motor with EM brake |
|------------------------|--|
| Horse Power (hp) | 6.7 |
| Output Rating (kW) | 5 |
| Motor Control Unit (A) | 400 |
| Max. Speed (km/h) | 25 |
| Drive Train | Motor shaft direct drive |
| Transaxle | Differential with Helical gears |

Optional Accessories

Steel Wheel
TPMS (Tire Pressure Monitoring System)

Warranty

| Warranty (year) | 1 |
|-----------------|------------------------------|
| Warranty Policy | On Manufacturing Defect Only |